

熊本空港(RJFT)に着陸する場合の無線要領Ⅱ (TCA 利用)

例：鹿児島空港 (RJFK) → 熊本空港 (RJFT)

FREQUENCY CHANGE ⇒ [KUMAMOTO TCA: 123.85MHz]

P : KUMAMOTO TCA, JA4319.

C : 4319, KUMAMOTO TCA. Go ahead.

P : 4319, 5,500,VFR,depart KAGOSHIMA, destination KUMAMOTO.

Request Radar Advisory.

C : 4319, SQUEAK 1234 & Ident. ⇒ read back, set & ident.

C : 4319, Radar contact

~

C : 4319, traffic 11 o'clock, four miles, 5,500, proceeding east.

P : 4319, Looking out / traffic insight / negative contact.

~

Reporting Point に近くなったら

[KUMAMOTO ATIS: 128.8MHz] ⇒ (Write down ATIS information)

FREQUENCY CHANGE ⇒ Cont` [KUMAMOTO TCA: 123.85MHz]

~

C : 4319, Contact Tower, 118.7. ⇒ read back.

FREQUENCY CHANGE ⇒ [KUMAMOTO TWR: 118.7MHz]

P : KUMAMOTO Tower, JA4319.

C : 4319, KUMAMOTO Tower. Go ahead.

P : 4319, over MIFUNE at 3500ft. Request landing, with information Delta.

C : 4319, runway 07, report right base. ⇒ read back.

~

P : 4319, join right base R/W 07.

C : 4319, R/W 07 cleared to land, wind 060 at 9..

P : 4319, R/W 07, cleared to land.

----- TOUCH DOWN

C : 4319, turn right Tango 3. Contact Ground. ⇒ read back.

FREQUENCY CHANGE ⇒ [KUMAMOTO GND: 121.8MHz]

P: KUMAMOTO Ground, JA4319 at Tango 3. Request taxi to Papa apron.

C: 4319, roger. Taxi to Papa apron. (事前に要調整)

熊本空港(RJFT)を離陸する場合の無線要領Ⅱ (TCA 利用)

例：熊本空港(RJFT) → 鹿児島空港(RJFK) プラン：関西 FAIB 050-3198-2866

① 出発前の TCA Advisory 要求

[KUMAMOTO ATIS: 128.8MHz] ⇒ (Write down ATIS information)

FREQUENCY CHANGE ⇒ [KUMAMOTO GND: 121.8MHz]

P : KUMAMOTO Ground, JA4319 with information Charlie.

C : 4319, KUMAMOTO Ground. Go ahead.

P : 4319 at Papa apron. VFR to KAGOSHIMA, request taxi to Tango4
for intersection departure and TCA advisory.

C : 4319, intersection departure approved, taxi to Tango 4. Contact tower
when ready.

P : 4319, taxi to Tango 4. Contact tower when ready.

FREQUENCY CHANGE ⇒ [KUMAMOTO TWR: 118.7MHz]

P : KUMAMOTO Tower, JA4319 at Tango 4 ready, request straight out
Departure.

C : 4319, straight out departure approved. Wind 270 at 7, R/W 25 cleared for
takeoff.

P : 4319, straight out departure approved. R/W 25 cleared for takeoff.

----- TAKEOFF

C : 4319, contact TCA 123.85.

P : 4319, contact TCA 123.85.

FREQUENCY CHANGE ⇒ [KUMAMOTO TCA: 123.85MHz]

P : KUMAMOTO TCA, JA4319.

C : 4319, KUMAMOTO TCA. Go ahead.

P : 4319, leaving 1,000 climbing 4500 VFR depart KUMAMOTO
destination KAGOSHIMA Request Radar Advisory.

C : 4319, SQUEAK 1234 & Ident. ⇒ read back, set & ident.

C : 4319, Radar contact

~